timenet

TIME MANAGEMENT SYSTEMS

Timenet is a complete Time and Attendance, Data Collection and Access Control system for up to 1,000 personnel.

It may be just connected to a printer for printing built-in reports, or connected to an Ethernet network for PC setup, data storage and report facilities.

Additional terminals can be connected using Ethernet or RS485 networking to provide extra clocking points and access terminals.

Timenet works in real-time, which means that employees can check their balances as they clock.

TIMENET SYSTEM TERMINAL

- Up to 1,000 personnel
- Full Flexitime facilities
- 250 shifts patterns including Fixed, Rotating and Continental Shifts
- 250 Departments
- 100 absence type individually programmable in employee calendars
- 7 overtime bands using 7day timezones, daily and weekly limits
- Multi-site Operation
- Multi-User PC software
- Extensive reporting with additional user writeable report facilities
- Automatic daily backups
- Magnetic cards, Proximity cards, Proximity keyfobs, Barcodes and Biometrics
- Web browser, PC and telephone clocking options
- Link to major payroll packages
- Automatic timed relay outputs for lunch break bells
- Realtime Attendance Display on PC screens
- Configurable Human Resources Database
- Editing of all clockings with full audit trail
- Infringement reporting including lateness, absences, core time
- Working Time Directive Report and Fire Report
- Battery backed operation
- Controls up to 100 Timenet and Access slave terminals.
- 40 characters by 2 line backlit LCD (Liquid Crystal Display).
- 45 key alphanumeric keyboard.
- Fire Alarm input and Relay outputs.
- Ethernet and RS485 network connections.

JMF

DESIGNED AND MANUFACTURED IN THE UK

ISO 9001
REGISTERED FIRM
QMS

TIMENET NETWORKING

System terminals may have additional slave terminals connected to provide extra clocking points and slave terminals may be of any type, connected using RS485 or Ethernet, depending on the terminal. It is also possible to use multiple system terminals, usually for separate buildings or sites and these are connected using modems or Ethernet and can use simple broadband connections or VPN's.

ORDERING INFORMATION

T002-CARD	Timenet Terminal with magnetic card reader.
T002-PROX	Timenet Terminal with proximity reader.
T002-BIO	Timenet Terminal with fingerprint reader.
T002-BLUE	Timenet Terminal with Bluetooth reader.

SPECIFICATIONS

Dimensions	290mm(W) x 160mm(H) x 80mm(D)	
Weight	3Kg	
Power Supply	12V DC	500mA
Connections	Vin, Vout, Gnd	Power In / Out
	TX+, TX-	RS485 connection
	Relay 1	Bell Relay
	Relay 2	Extra Relay
	Opto-isolated input	Fire Alarm input 12-24V
	RS232 output	Printer output
	RJ45 Ethernet port	
Environment	Temperature	0 - 40C
	Humidity	15%-90% Non-Condensing
Terminal Network	Maximum of 100 terminals	